



CONSOLIDATED BEARING trading LTD



15 mm x 35 mm x 19 mm SKF NUTR 15 A Cam Follower and Track Roller - Yoke Type

Bearing No. NUTR 15 A

NUTR 15 A Bearing 2D drawings and 3D CAD models

Category	Cam Follower and Track Roller - Yoke Type
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.1
Product Group	B04144
Roller Surface Profile	Crowned
Profile	Yoke Type
Enclosure	Sealed
Rolling Element	Cylindrical Roller Bearing - Double Row
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Full Complement With Flanged Inner Ring Labyrinth Seal
Long Description	15MM Bore; 35MM Roller Diameter; 18MM Roller Width; Crowned Roller; Yoke Type; Sealed; Cylindrical Roller Bearing - Double Row; Relubricatable
Category	Cam Followers Yoke Type
UNSPSC	31171530
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Keyword String	Cam Follower



CONSOLIDATED BEARING trading LTD

Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NUTR 15 A
Weight / LBS	0.22
Roller Diameter	1.378 Inch 35 Millimeter
Roller Width	0.709 Inch 18 Millimeter
d	0.591 Inch 15 Millimeter
roller diameter:	35 mm
radial static load capacity:	12.2 kN
roller width:	19 mm
roller material:	Chrome Steel
bore diameter:	15 mm
maximum rpm:	5000 RPM
roller shape:	Crowned
lubrication hole location:	Inner Ring
bearing element:	Cylindrical Rollers
axial dynamic load capacity:	16.8 kN
closure type:	Sealed
axial static load capacity:	17.6 kN
operating temperature range:	Maximum of +280 ° F
finish/coating:	Uncoated
radial dynamic load capacity:	8.65 kN
standards met:	ANSI/ABMA Standard 18.1
D	35 mm
d	15 mm
C	18 mm
B	19 mm
d ₁	20 mm
r _{1,2} min.	0.6 mm
r, r _{3,4} min.	0.3 mm
Basic dynamic load rating C	16.8 kN
Basic static load rating C ₀	17.6 kN



CONSOLIDATED BEARING trading LTD

Fatigue load limit P_u	2 kN
Maximum dynamic radial loads F_r max.	8.65 kN
Maximum static radial loads F_{0r} max.	12.2 kN
Limiting speed	5000 r/min
Mass support roller	0.099 kg