



# CONSOLIDATED BEARING trading LTD



NUTR 30 X Bearing 2D drawings and 3D CAD models

30 mm x 62 mm x 29 mm SKF NUTR 30 X Cam Follower and Track Roller - Yoke Type

Bearing No. NUTR 30 X

|                        |   |
|------------------------|---|
| Category               | Cam Follower and Track Roller - Yoke Type   |
| Inventory              | 0.0   |
| Manufacturer Name      | SKF   |
| Minimum Buy Quantity   | N/A   |
| Weight                 | 0.47  |
| Product Group          | B04144  |
| Roller Surface Profile | Flat  |
| Profile                | Yoke Type   |
| Enclosure              | Sealed  |
| Rolling Element        | Cylindrical Roller Bearing - Double Row   |
| Relubricatable         | Yes   |
| Inch - Metric          | Metric  |
| Other Features         | Full Complement   With Flanged Inner Ring   Labyrinth Seal  |
| Long Description       | 30MM Bore; 62MM Roller Diameter; 28MM Roller Width; Flat Roller; Yoke Type; Sealed; Cylindrical Roller Bearing - Double Row; Relubricatable |
| Category               | Cam Followers Yoke Type   |
| UNSPSC                 | 31171530  |
| Harmonized Tariff Code | 8482.50.00.00   |
| Noun                   | Bearing   |
| Keyword String         | Cam Follower  |
|                        |   |



## CONSOLIDATED BEARING trading LTD

|  |   |
|--|---|
| Manufacturer URL                                 | <a href="http://www.skf.com">http://www.skf.com</a> |
| Manufacturer Item Number                         | NUTR 30 X   |
| Weight / LBS                                     | 1.036   |
| Roller Width                                     | 1.102 Inch   28 Millimeter                          |
| d  | 1.181 Inch   30 Millimeter                          |
| Roller Diameter                                  | 2.441 Inch   62 Millimeter                          |
| D  | 62 mm   |
| d  | 30 mm   |
| C  | 28 mm   |
| B  | 29 mm   |
| d <sub>1</sub>                                   | 38 mm   |
| r <sub>1,2</sub> min.                            | 1 mm  |
| r, r <sub>3,4</sub> min.                         | 0.5 mm  |
| Basic dynamic load rating C                      | 41.3 kN   |
| Basic static load rating C <sub>0</sub>          | 47.5 kN   |
| Fatigue load limit P <sub>u</sub>                | 5.85 kN   |
| Maximum dynamic radial loads F <sub>r</sub> max. | 24 kN   |
| Maximum static radial loads F <sub>0r</sub> max. | 34.5 kN   |
| Limiting speed                                   | 2600 r/min  |
| Mass support roller                              | 0.47 kg   |