



CONSOLIDATED BEARING trading LTD



6064 NSK Deep groove ball bearings

Bearing No. 6064

| | |
|-------------------------------|---------------|
| Size | 320x480x74 mm |
| Bore Diameter | 320 mm |
| Outer Diameter | 480 mm |
| Width | 74 mm |
| d | 320 mm |
| D | 480 mm |
| B | 74 mm |
| C | 74 mm |
| r min. | 4 mm |
| da min. | 350 mm |
| Da max. | 454 mm |
| ra max. | 3 mm |
| Weight | 46,5 Kg |
| Basic dynamic load rating (C) | 390 kN |
| Basic static load rating (C0) | 570 kN |
| SRI | 26.29 |
| hidYobi | 6064 |
| LangID | 1 |
| D_ | 480 |
| SREX | 0.1 |
| B_ | 74 |
| da min | 336 |
| hidTable | ecat_NSRDGB |
| Oil rpm | 1300 |
| SRE | 26.29 |
| mass | 46.5 |

6064 Bearing 2D drawings and 3D CAD models



CONSOLIDATED BEARING trading LTD

| | |
|------------|------------|
| GRS rpm | 1100 |
| ra | 3 |
| SRIX | 0.1 |
| D_a | 464 |
| SRIN | -0.1 |
| C0 | 570 |
| fo | 15.7 |
| SREN | -0.1 |
| DE_ | 450.8 |
| Prod_Type3 | DGBB_SR_OT |
| DA_ | 50.8 |
| bomp | 0 |
| Z_ | 14 |
| yobi | 6064 |
| C_conv | 390000 |
| ALPHA_ | 0 |
| SDM_ | 400 |
| r | 4 |
| KBRG | 6104 |
| SBRG | 10 |
| DI_ | 349.2 |